

**OCF “Gaborone-1” – Adding support of oic.if.rw to all OCF SVRs – Security WG CR
3101**

Legal Disclaimer

THIS IS A DRAFT SPECIFICATION DOCUMENT ONLY AND HAS NOT BEEN ADOPTED BY THE OPEN CONNECTIVITY FOUNDATION. THIS DRAFT DOCUMENT MAY NOT BE RELIED UPON FOR ANY PURPOSE OTHER THAN REVIEW OF THE CURRENT STATE OF THE DEVELOPMENT OF THIS DRAFT DOCUMENT. THE OPEN CONNECTIVITY FOUNDATION AND ITS MEMBERS RESERVE THE RIGHT WITHOUT NOTICE TO YOU TO CHANGE ANY OR ALL PORTIONS HEREOF, DELETE PORTIONS HEREOF, MAKE ADDITIONS HERETO, DISCARD THIS DRAFT DOCUMENT IN ITS ENTIRETY OR OTHERWISE MODIFY THIS DRAFT DOCUMENT AT ANY TIME. YOU SHOULD NOT AND MAY NOT RELY UPON THIS DRAFT DOCUMENT IN ANY WAY, INCLUDING BUT NOT LIMITED TO THE DEVELOPMENT OF ANY PRODUCTS OR SERVICES. IMPLEMENTATION OF THIS DRAFT DOCUMENT IS DONE AT YOUR OWN RISK AMEND AND IT IS NOT SUBJECT TO ANY LICENSING GRANTS OR COMMITMENTS UNDER THE OPEN CONNECTIVITY FOUNDATION INTELLECTUAL PROPERTY RIGHTS POLICY OR OTHERWISE. IN CONSIDERATION OF THE OPEN CONNECTIVITY FOUNDATION GRANTING YOU ACCESS TO THIS DRAFT DOCUMENT, YOU DO HEREBY WAIVE ANY AND ALL CLAIMS ASSOCIATED HERewith INCLUDING BUT NOT LIMITED TO THOSE CLAIMS DISCUSSED BELOW, AS WELL AS CLAIMS OF DETRIMENTAL RELIANCE.

The OCF logo is a trademark of Open Connectivity Foundation, Inc. in the United States or other countries. *Other names and brands may be claimed as the property of others.

Copyright © 2020 Open Connectivity Foundation, Inc. All rights reserved.

Copying or other form of reproduction and/or distribution of these works are strictly prohibited.

Table 1 – Definition of the "/oic/sec/doxm" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/doxm	Device OTMs	oic.r.doxm	oic.if.baseline, oic.if.rw	Resource for supporting Device owner transfer	Configuration

Table 2 – Definition of the "/oic/sec/cred" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/cred	Credentials	oic.r.cred	oic.if.baseline, oic.if.rw	Resource containing credentials for Device authentication, verification and data protection	Security

Table 3 – Definition of the "oic/sec/acl2" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/acl2	ACL2	oic.r.acl2	oic.if.baseline, oic.if.rw	Resource for managing access	Security

Table 4 – Definition of the "/oic/sec/pstat" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/pstat	Provisioning Status	oic.r.pstat	oic.if.baseline, oic.if.rw	Resource for managing Device provisioning status	Configuration

Table 5 – Definition of the "/oic/sec/csr" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/csr	Certificate Signing Request	oic.r.csr	oic.if.baseline, oic.if.rw	The CSR resource contains a Certificate Signing Request for the Device's public key.	Configuration

Table 6 – Definition of the "/oic/sec/roles" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/roles	Roles	oic.r.roles	oic.if.baseline, oic.if.rw	Resource containing roles that have previously been asserted to this Server	Security

Table 7 – Definition of the "/oic/sec/sp" Resource

Fixed URI	Resource Type Title	Resource Type ID ("rt" value)	OCF Interfaces	Description	Related Functional Interaction
/oic/sec/sp	Security Profile Resource Definition	oic.r.sp	oic.if.baseline, oic.if.rw	Resource specifying supported and current security profile(s)	Discoverable

IN CLAUSE C.1

Change every instance of

"enum" : ["oic.if.baseline"]

To

"enum" : ["oic.if.baseline", "oic.if.rw"]